


Models	L (mm)	A (mm)	B (mm)	C (mm)
SG4-xx-030-00-P	306,3	86,3	110	-
SG4-xx-045-00-P	456,3	236,3	110	-
SG4-xx-060-00-P	606,3	306,2	150	-
SG4-xx-075-00-P	756,2	406,2	175	-
SG4-xx-090-00-P	906,1	506,1	200	-
SG4-xx-105-00-P	1056,1	606,1	225	-
SG4-xx-120-00-P	1206	966	150	453
SG4-xx-135-00-P	1356	1066	175	503
SG4-xx-150-00-P	1505,9	1166	200	553
SG4-xx-165-00-P	1655,9	1266	225	603
SG4-xx-180-00-P	1805,8	1366	250	652,9

MOD.	REV.	PROPOSAL	DESCRIPTION.		DATE	SIGN
All materials employed have to be selected among RoHS compliant materials: the EC directives to be referred to are 2002/95/EC and correlated subsequent ones.						
DIMENSIONS WITHOUT TOLERANCE DEGREE: .. according to ISO 2768				NOTE		
PRECISION DEGREE		DIMENSIONAL GROUPS			TREAT.	
		> 0 A 6	> 6 A 30	> 30 A 120	> 120 A 315	> 315 A 999
MEDIUM (m)		± 0,1	± 0,2	± 0,3	± 0,5	± 0,8
PRECISE (P)		± 0,05	± 0,1	± 0,15	± 0,2	± 0,3
DES. BY L. Rossetti				DATE 26/10/2011		APPROV. .
 www.datalogic.com				NAME Standard bracket mounting distances		MOLD N° .
						CODE
						PART N° DIM-0708
				SCALE 1:2		